# Martin Synchronous Sprocket Nomenclature









**MPC®** 

High HP HTS®

HTS®
(High Torque Sprocket)

**Timing Pulley** 

#### **MPC®**

Tooth profile compatible with most popular modified curvilinear belts

Bushing Options  PB Minimum Plain Bore No prefix Taper Bushed or QD	PB	8MX	225	12 - SH	Bushing Option QD JA, SH, SDS S TB 1008, 1108 120100
Belt Pitch					Belt Width (mm)
8mm 14mm					12, 21, 36, 62 20, 37, 68, 90, 125
Number of Teeth					

<sup>&</sup>quot;S" identifies it as an MPC

#### **HTS®**

RPP tooth profile, runs with: Hawk Pd®, RPP®, RPP+® HTD belts

# P 30 14M 55 - SK

HTS®	Bushing
Number of Teeth	or MPB
Belt Pitch	Belt Width (mm)
5mm	15, 25
8mm	20, 30, 50, 85
14mm	40, 55, 85, 115, 170
20mm	115, 170, 230, 290, 340

### High HP HTS®

RPP tooth profile, runs with: Hawk Pd®, Panther®, QT Power Chain® belts

W 24 8M 22 - JA

Hight HP HTS®	Bushing
	or MPB
Number of Teeth	
Belt Pitch	Belt Width (mm)
8mm	12, 22, 35, 60
14mm	20, 42, 65, 90, 120

# **Timing Pulleys**

Tooth profile compatible with trapezoidal tooth belts

TB Bushing		ТВ	18		L 100	JA	Bushing Option			
If listed, denotes the and drilled to accept	T			<b>QD</b> JA, SH, SDS S <b>TB</b> 1008, 1108 120						
Number of Teeth					Belt Width					
Belt Pitch							037	3/8"		1 1/2"
XL Extra Light	1/5"						050	1/2"	200	
	3/8"						075	3/4"	300	
<b>L</b> Light							100	1"	400	4"
<b>H</b> Heavy	1/2"									
XH Extra Heavy	7/8"									

Fast MTO Deliveries • Stainless Steel • Aluminum • Non-Metallic
Custom Labeling & Kitting • Special Bores • Staged for scheduled releases from local Manta Plant

martinsprocket.com • 817.258.3000

Copyright® 2019 Martin Sprocket & Gear, Inc. • All Rights Reserved • CARD-SYNCHR • 1/18/2019