

**MetaliCom 7" TFT LCD Monitor with VGA and AV inputs
MetaliCom Model# MC-700STP**



| | |
|--------------------------------|---------------------------------------|
| Screen Size | Diagonal 7" (16:9) |
| Physical Resolution | 800 (H) x 480 (V) WVGA |
| Supported Resolution | 640 x 480 ~ 1600 x 1200 |
| Dot Resolution | 2400 x 480 = 1,152,000 (dots) |
| LCD Brightness | 500cd/m2 LED Backlight (Typ) |
| Contrast Ratio | 400:1 |
| Viewing Angle | 160° Horizontal, 140° Vertical |
| Touch Screen Interface | 10 - 15ms |
| Operating Voltage Range | DC 11V ~30V |
| Power Supply | DC 12V |
| Power Consumption | ≤ 10W |
| Operating Temperature | -10°C ~ +70°C |
| Storage Temperature | -°F ~ 176°F |
| Dimension (in) | 191(W) x 121(H) x 33(D) |
| Weight (lb) | 500 |
| | With 5 Wire Touch Screen |
| | FCC, CE, E13 Certification |
| | ROHS Compliant |

MetaliCom 7" TFT LCD Monitor with VGA and AV inputs
MetaliCom Model# MC-700STP

Features

- For In-Car Computing, PC, Server, GPS, and various VGA Use
- High Bright LCD Panel with LED Backlight *New*
- VGA Input x 1 & Video Input x 2
- Audio Input x 1 / Built-in Speaker
- NTSC / PAL Multi-System
- 16x9 Aspect Ratio
- High Resolution Display
- Upgraded High-Brightness LED Backlight 500 nit(Typ)
- Pixel works High Performance Image and Video Signal Processor
- 16:9 / 4:3 Scale settings
- Last Input memory
- Last Power setting memory
- IR Remote Control
- Auto power-on upon signal detection
- Automatic display adjustment
- On Screen Display Control
- Mirror Image Flip
- Vertical Image Flip
- AV2 Auto Switching for backup camera
- Supports 12V DC ~ 32V DC
- "E" Mark Certified for Automotive use

Accessories

- Instruction Manual
- Installation CD
- Monitor stand
- US or European AC adaptor
- Multi-Connection Cable
- Remote Control (Optional)
- Cigarette plug charger (Optional)



www.MetaliCom.com